



HYDROSTRAW® CELLULOSE FIBER PLUS CERTIFICATE OF COMPLIANCE


CERTIFICATE OF COMPLIANCE

Patents Pending

Manufacturer: HydroStraw, LLC 22110 S. State Route 27 Rockford, WA 99030

Toll Free: 800-545-1755 Fax: 815-468-7450 www.hydrostraw.com info@hydrostraw.com

HydroStraw, LLC certifies that HydroStraw® Cellulose Fiber Plus contains the following properties and characteristics




DESCRIPTION

HydroStraw® Cellulose Fiber Plus is a hydraulically applied mulch with a specially formulated composition of annually renewable wheat straw fibers, cellulose fibers, natural fibers for fiber matrix entanglement, and a non toxic soil stabilizer.

SPECIFICATIONS

The primary fibers shall be produced from annually renewable wheat straw fiber and cellulose fiber; all fiber materials should be free from plastic materials or other non bio-degradable substances. Fiber shall not contain recycled news print or ink. Fiber shall be of such character that the fiber will disperse into a uniform slurry when mixed with water. Fiber shall be colored green and shall not stain concrete or other surfaces. Fiber and other mulch ingredients shall be free from growth or germination inhibiting ingredients. Mulch Fiber shall be applied as a slurry solution by means of hydroseeder.

Increased performance can be achieved by mixing infield a hydro-colloid tackifier such as guar per manufacturer's recommended rates. It is imperative that the mulch be applied at the specified rate: too wet of a mixture will cause the fibers to be buried into soil. Mulch Fiber shall be applied as a slurry solution by means of hydroseeding. Mulch Fiber shall be applied at the specified rate per the specifications in a uniform manner. Care shall be exercised to ensure that the mulch application is uniform and even throughout the seeded area; mulch shall not be bunched or clumped up on the site. Care shall also be taken as to not create a shadowing effect on the site, mulch applications shall be started on the windward side of the project.



WARRANTY

HydroStraw, LLC warrants that its products are free from defects and will perform as stated in this literature. If our product does not meet products specifications, notice of failure must be received within 15 days of failure. HydroStraw, LLC will not warrant that the product will perform under unlimited circumstances that are caused by soil conditions, installation, and/or weather variables.

Physical Characteristics	
Toxicity	Non Toxic
Applied Color	Green
Surface Tension	Material will evenly disperse and suspend when agitated in water
Absorbency	When sprayed uniformly at the recommended rate, the mulch fibers form an absorbent mulch cover which will allow percolation of water and increased water infiltration to the underlying soil matrix
Solubility	Mulch Fibers are Non Water Soluble
pH	6.8 +/- 0.5
Average Fiber Length	1/2" +/- 1/4" (1.27 cm +/- .64 cm)

Packaging and Shipping Data	
Bag Size	11.5" x 17" x 25" (29.2 x 43 x 63.5 cm)
Bag Weight	50 lb (22.7 kg)
Pallet	40 Bags, 52" x 45" x 96" (132 x 114 x 244 cm)
Full Truck	22 Pallets, 880 Bags
Packaging	Moisture Resistant Packaging

Composition	
Heat & Mechanically Treated™ (HMT) - Wheat Straw	54.0% +/- 1.0%
Cellulose Fibers	30.0% +/- 1.0%
Natural Fibers	4.0% +/- 1.0%
Moisture	10.0 +/- 1.0%
Non-Toxic Soil Stabilizer	2.0 +/- 1.0%

Mixture Rates	
Hose Work	60 lbs / 100 gallons (27 kg / 379 liters)
Tower Work	75 lbs / 100 gallons (34 kg / 379 liters)

*Hose Work Rate may vary dependent on hydroseeder type and/or size and length of hose used.

SLOPE GRADIENT / CONDITION	LB / ACRE	KG / HECTARE
≤ 4:1	2,000	2,250
≤ 3:1	2,000 - 3,000	2,250 - 3,350
≤ 2:1	3,000 - 4,000	3,350 - 4,500
Soil Moisture Retention	2000 - 3,500	2,250 - 4,000